

ELECTRICAL DATA AT STC*

Power Output (Pmax)	5 W
Power tolerance	0-5 %
Module Efficiency	9.45 %
Maximum Power Voltage (Vmp)	18.82 V
Maximum Power Current (Imp)	0.36 A
Open Circuit Voltage (Voc)	23.69 V
Short Circuit Current (Isc)	0.38 A

*Standard Test Conditions; Irradiance: 1000W/m², Cell temperature: 25°C, AM:1.5

MECHANICAL CHARACTERISTICS

Cell Type	Polycrystalline
Number of Cells	36
Dimensions	210*252*18mm
Weight	0.6kg
Glass	3.2mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP65
Cable	without
Connector	without
Connector	without



TEMPERATURE CHARACTERISTICS

NOCT	45°C±2°C
Temperature coefficient of Pmax	-0.41%/K
Temperature coefficient of Voc	-0.31%/K
Temperature coefficient of Isc	+0.06%/K

MAXIMUM RATINGS

Operating temperature range	-45°C~+85°C
Maximum system voltage	1000 V
Max series fuse rating	10 A
Max front load (e.g.: snow)	5400 Pa
Max back load (e.g.: wind)	2400 Pa

SA5-36P



SINOSOLA®

Yuhuan Sinosola Science & Technology Co., Ltd

No. 53, Fugang Road, Bingang Industrial Park, Shamen Town, Yuhuan, Taizhou, Zhejiang, 317607, China
Tel.: +86 576 8733 9881
www.sinosola.cn



Solar Brasil Tecnologia & Energia Fotovoltaica Ltda

Rua braganca paulista, 102 Vila Cruzeiro, San Paulo, CEP 04727-000, Brasil
Tel.: (11) 2305-7452 / (11) 2305-7448 / (11) 5542-7980 / (11) 5041-7666
www.solarbrasil.com.br